(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

(10) International Publication Number WO 2004/114583 A2

(51) International Patent Classification7: H04N 7/24, 5/00, 7/66, 7/62

H04L 7/04.

(21) International Application Number:

PCT/US2004/019357

(22) International Filing Date:

16 June 2004 (16.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/479,395

18 June 2003 (18.06.2003)

(71) Applicant (for all designated States except US): THOM-SON LICENSING S.A. [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne (FR).

(72) Inventors; and


(75) Inventors/Applicants (for US only): MARKMAN. Ivonete [BR/US]; 11388 Royal Court, Carmel, Indiana 46032 (US). LIU, Weixiao [CN/US]; 9353 D College Drive, Indianapolis, Indiana 46240 (US). HORLANDER,

Thomas, Edward [US/US]; 6234 Haverford Avenue, Indianapolis, Indiana 46220 (US). MAYER, Matthew, Thomas [US/US]; 8262 Forest Lane, Indianapolis, Indiana 46240 (US).

- (74) Agents: TRIPOLI, Joseph, S. et al.; c/o Thomson Licensing Inc., 2 Independence Way, Suite 200, Princeton, New Jersey 08540 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR FALSE SYNC LOCK DETECTION IN A DIGITAL MEDIA RECEIVER



(57) Abstract: A method and apparatus (400) for identifying a false MPEG-2 packet synchronization lock condition by parsing MPEG-2 packets that may have been incorrectly delineated by a sync-byte checksum-decoder, to detect resulting anomalies. Forcing the restart of the conventional checksum-encoded sync-byte synchronization/lock process upon generating a "resync" command based upon the anomalies detected by a False Lock Detector. Reliably synchronizing and delivering the MPEG-2 stream to the receiver transport layer. The False-Lock Detector circuit compares the content of the currently identified packet header or payload portion of a sync-byte delineated packet with expected values in order to detect a false-lock condition and to eliminate false sync-byte position-candidates from the basis of a "synchronization lock".

WO 2004/114583 A2



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

(10) International Publication Number WO 2004/114583 A3

(51) International Patent Classification7: H04N 7/24, 5/00, 7/66, 7/62

H04L 7/04,

(21) International Application Number:

PCT/US2004/019357

(22) International Filing Date: 16 June 2004 (16.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/479,395

18 June 2003 (18.06.2003) US

- (71) Applicant (for all designated States except US): THOM-SON LICENSING S.A. [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne (FR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MARKMAN, Ivonete [BR/US]; 11388 Royal Court, Carmel, Indiana 46032 (US). LIU, Weixiao [CN/US]; 9353 D College Drive, Indianapolis, Indiana 46240 (US). HORLANDER, Thomas, Edward [US/US]; 6234 Haverford Avenue, Indianapolis, Indiana 46220 (US). MAYER, Matthew, Thomas [US/US]; 8262 Forest Lane, Indianapolis, Indiana 46240 (US).


- (74) Agents: TRIPOLI, Joseph, S. et al.; c/o Thomson Licensing Inc., 2 Independence Way, Suite 200, Princeton, New Jersey 08540 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR FALSE SYNC LOCK DETECTION IN A DIGITAL MEDIA RECEIVER



(57) Abstract: A method and apparatus (400) for identifying a false MPEG-2 packet synchronization lock condition by parsing MPEG-2 packets that may have been incorrectly delineated by a sync-byte checksum-decoder, to detect resulting anomalies. Forcing the restart of the conventional checksum-encoded sync-byte synchronization/lock process upon generating a "resync" command based upon the anomalies detected by a False Lock Detector. Reliably synchronizing and delivering the MPEG-2 stream to the receiver transport layer. The False-Lock Detector circuit compares the content of the currently identified packet header or payload portion of a sync-byte delineated packet with expected values in order to detect a false-lock condition and to eliminate false sync-byte position-candidates from the basis of a "synchronization lock".



(88) Date of publication of the international search report: 24 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.